



Corrigendum

Corrigendum to “Data driven model for heat load prediction in buildings connected to District Heating by using smart heat meters” [Energy 239, Part D, 2022, 122318]



Mikel Lumbreras ^{a,*}, Roberto Garay-Martinez ^b, Beñat Arregi ^b,
Koldobika Martin-Escudero ^a, Gonzalo Diarce ^a, Margus Raud ^c, Indrek Hagu ^c

^a ENEDI Research Group, Department of Energy Engineering, Faculty of Engineering of Bilbao, University of the Basque Country UPV/EHU, Pza. Ingeniero Torres Quevedo 1, Bilbao, 48013, Spain

^b TECNALIA, Basque Research and Technology Alliance (BRTA), Bizkaia Science and Technology Park, Astondo Bidea 700, Derio, Spain

^c GREIN Eesti, Turu 18, Tartu, Estonia

The authors regret to inform that, even after careful revisions in all stages of the manuscript, a relevant typographic error has been found in the published version of the paper. The error is found in the definition of the so-called Q-algorithm in Eq. (1), where the selection among two formulae is performed based on the actual heat load (Q) compared to a reference heat load (Q_{REF}). The correct formulation for equation can be found in Eq. (1) below.

$$Q_{\text{alg}} = \begin{cases} \alpha_1 \cdot T_{\text{OUT}} + \alpha_2 \cdot G_T + \alpha_3 \cdot W_S + \alpha_4 \cdot W_D, & Q > Q_{\text{REF}} \\ \alpha_0, & Q \leq Q_{\text{REF}} \end{cases} \quad (1)$$

The authors would like to apologise for any inconvenience caused.

DOI of original article: <https://doi.org/10.1016/j.energy.2021.122318>.

* Corresponding author.

E-mail address: mikel.lumbreras@ehu.eus (M. Lumbreras).